



Features

- ▶ High video quality on HD 1080P
- ▶ Long transmission distance
- ▶ Support CoC (UTC) to Operate
- ▶ Megapixels f3.6mm Lens
- ▶ 20 Meter with 24pcs. LEDs IR
- ▶ Digital wide Dynamic Range
- ▶ IP66 Water proff



SPECIFICATION

SPECIFICATION	KP-H902AN
VIDEO	
Image Sensor	2.0MP 1/2.9" CMOS
Resolution	1920 x 1080
Lens	3.0MP f3.6 Lens
IRIS Control	N/A
Minimum Illumination	0.1Lux@F1.6(Color), 0.01Lux@F1.6(B/W IR on)
S/N Ratio	50dB (AGC off)
Electronic Shutter Speed	1/25s ~ 1/50,000s , 1/30s ~ 1/60,000
Day/Night	IR cut lter with auto switch
IR LEDs	24pcs. LEDs IR
Video Out	AHD/CVI/TVI@1080P, 960H SD
FUNCTION	
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	Yes
HSBLC	N/A
Motion Detection	N/A
Privacy Masking	N/A
Day&Night	Auto/Color/B&W
White Balance	Auto/Manual
Digital Noise Reduction	2D/3D DNR
Mirror	N/A
De-fog	N/A
OSD Language	EN, CN, GE, FREN, IT, SP, PO, RU
ENVIRONMENTAL	
Out-Door Ready	IP66
Operating Temperature	-10 °C ~ 50 °C , RH95% Max
ELECTRICAL	
Power Source	DC 12V(10%)
MECHANICAL	
Dimensions(HxWxD)	Ø106.5 x 65mm
Weight	T.B.D