

KP-H911AN

Features

- ▶ high video quality on HD 1080P
- ▶ Long transmission distance
- ▶ Support CoC(UTC) to operate OSD MENU
- ▶ Megapixel f3.6mm Lens
- ▶ 35 Meter with LEDs IR
- ▶ Digital Wide Dynamic Range
- ▶ IP66 water proff



SPECIFICATION

SPECIFICATION	KP-H911AN
VIDEO	
Image Sensor	2.0MP 1/2.9" CMOS
Resolution	1920 x 1080
Lens	Megapixels f3.6 Lens
IRIS Control	N/A
Angular Field of view	T.B.D
Minimum Illumination	0.1Lux@F1.6(Color),0.01Lux@F1.6(B/W IR on)
S/N Ratio	50dB (AGC off)
Electronic Shutter Speed	1/25s ~ 1/50,000s , 1/30 ~ 1/60,000s
Day/Night	IR cut lter with auto switch
IR LEDs	36pcs. LEDs IR; 35M
Video Out	AHD/CVI/TVI@1080P, 960H SD
FUNCTION	
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	Yes
HSBLC	N/A
Motion Detection	N/A
Privacy Masking	N/A
Day&Night	Auto/Color/B&W
White Balance	Auto/ Manual
Digital Noise Reduction	2D/3D DNR
Mirror	N/A
De-fog	N/A
OSD Language	EN, CN, GE, FREN, IT, SP, PO, RU
ENVIRONMENTAL	
Out-Door Ready	IP66
Operating Temperature	-10° C ~ 50° C, RH95% Max
ELECTRICAL	
Power Source	DC 12V(10%)
MECHANICAL	
Dimensions(HxWxD)	66mm x 69mm x 163mm
Weight	T.B.D