

# KP-H912AN

www.kenprocctv.com | 02-2220559

## Features

- ▶ High video quality on HD 720P and HD 1080P
- ▶ HD 3 Megapixels f3.6mm Lens
- ▶ AHD, TVI, CVI and 960H
- ▶ Support CoC (UTC) to operate OSD MENU
- ▶ 6pcs. Blue Array LED 20M
- ▶ Digital Wide Dynamic Range

## SPECIFICATION

| SPECIFICATION                | KP-H912AN                              |
|------------------------------|--|
| <b>VIDEO</b>                 |  |
| Image Sensor                 | 1/2.7" 2.0M CMOS Sensor                |
| Resolution                   | 1920 x1080                             |
| Lens                         | HD 3 Megapixels f3.6mm                 |
| IRIS Control                 | N/A                                    |
| Angular Field of view        | 82.2                                   |
| Minimum Illumination         | 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR |
| S/N Ratio                    | 50dB (AGC off)                         |
| Electronic Shutter Speed     | 1/60s ~ 1/67,500s                      |
| Day/Night                    | IR cut lter with auto switch           |
| IR LEDs                      | 6pcs. Blue Array LED 20M               |
| Video Out                    | AHD/CVI/TVI@1080P, 960H SD             |
| <b>FUNCTION</b>              |  |
| WDR (Wide Dynamic Range)     | D-WDR                                  |
| BLC (Backlight Compensation) | Yes                                    |
| HSBLC                        | N/A                                    |
| Motion Detection             | N/A                                    |
| Privacy Masking              | N/A                                    |
| Day&Night                    | Ext/Auto/Color/B&W                     |
| White Balance                | Auto/Manual                            |
| Digital Noise Reduction      | 2D/3D DNR                              |
| Mirror                       | N/A                                    |
| De-fog                       | N/A                                    |
| OSD Language                 | Multi-language                         |
| <b>ENVIRONMENTAL</b>         |  |
| Operating Temperature        | -20°C ~ 50°C                           |
| <b>ELECTRICAL</b>            |  |
| Power Source                 | DC 12V(10%)                            |
| <b>MECHANICAL</b>            |  |
| Dimensions(HxWxD)            | 66mm x 69mm x 163mm                    |
| Weight                       | T.B.D                                  |

