



Features

- ▶ High video quality on HD 1080P
- ▶ Long transmission distance
- ▶ Support CoC (UTC) to Operate
- ▶ Vari-Focal f2.8 -12mm
- ▶ 40 meter with 48pcs. LEDs IR
- ▶ Digital wide Dynamic Range
- ▶ IP66 Water proff



SPECIFICATION

| SPECIFICATION | KP-H941AN-VF |
|------------------------------|---|
| VIDEO | |
| Image Sensor | 2.0MP 1/2.7" CMOS |
| Resolution | 1920 x 1080 |
| Lens | HD Lens f2.8-12mm @F1.8 |
| IRIS Control | N/A |
| Minimum Illumination | 0.1Lux@F1.6(Color), 0.01Lux@F1.6(B/W IR on) |
| S/N Ratio | 50dB (AGC off) |
| Electronic Shutter Speed | 1/25s ~ 1/50,000s , 1/30s ~ 1/60,000 |
| Day/Night | IR cut lter with auto switch |
| IR LEDs | 48pcs. LEDs IR; 40M |
| Video Out | AHD/CVI/TVI@1080P, 960H SD |
| FUNCTION | |
| WDR (Wide Dynamic Range) | D-WDR |
| BLC (Backlight Compensation) | Yes |
| HSBLC | N/A |
| Motion Detection | N/A |
| Day&Night | Auto/Color/B&W |
| White Balance | Auto/ Manual |
| Digital Noise Reduction | 2D/3D DNR |
| De-fog | N/A |
| OSD Language | EN, CN, GE, FREN, IT, SP, PO, RU |
| ENVIRONMENTAL | |
| Out-Door Ready | IP66 |
| Operating Temperature | - 10 °C to 50 °C , RH95% MAX |
| ELECTRICAL | |
| Power Source | DC 12V(10%) / 1A |
| MECHANICAL | |
| Dimensions(HxWxD) | 80mm x 90mm x 265mm |
| Weight | T.B.D |