

Features

- ▶ Day/Night functionality , IR Cut Removable
- ▶ Smart IR , up to 30m (98 ft) IR distance
- ▶ Optical glass window with higher light transmittance
- ▶ Angle of view(H)
- ▶ HLC (Highlight Compensation)
- ▶ H.265, H.264, MJPEG
- ▶ Embedded smart algorithm
- ▶ Triple streams
- ▶ 9 : 16 corridor format
- ▶ ONVIF Conformance
- ▶ Wide teperature range : -35 °C to 60 °C (-31 °F to 140 °F)



SPECIFICATION

Camera	
Sensor	1/2.7" , 2 Megapixel, Progressive scan CMOS
Shutter	Auto/Manual, 1/6 ~ 1/100000 s
Min. Illumination	Colour: 0.005 Lux (F1.8 , AGC ON) 0 Lux with IR on
Lens Mount	4.0 mm@ F 1.8
Day/Night	IR-cut lter with auto switch(ICR)
S/N	>52 dB
WDR	D-WDR
Video	
Compatible Integration	1920 x 1080
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	1080P (1920x1080): Max. 30fps; 720P (1280x720): Max. 30fps D1 (720x576): Max. 25 fps
Video Streaming	Triple
9:16 Corridor Mode	Supported
ROI	Up to 8 areas
HLC	Supported
Defog	Digital Defog
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Smart VCA	
Behavior Detection	Intrusion, crossing line, motion detection
Intelligent Identification	Face detection, Defocus, Scene change
Statistical Analysis	People counting
Audio	
Audio Compression	N/A
Two way audio	N/A
Storage	
Edge Storage	N/A
Network	
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SMTP, 802.1x, SNMP, SSL, TLS
Compatible Integration	ONVIF(Prole S), API
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
General	
Power	12 VDC 25%, or PoE(IEEE802.3 af) Power consumption : Max 6.4 W
Dimensions(L x W XH)	157.3 x 62.4 x 63 mm(6.2" x 2.5" x 2.5")
Weight	0.45 kg (0.99 lb)
Working Environment	-35°C to 60°C (-31°F to 140°F), Humidity 95% RH(non-condensing)
Ingress Protection	IP67