



KP-IP902P5NV

www.kenproctv.com | 02-2220559

SPECIFICATION

Features

- ▶ Day/Night functionality
- ▶ Smart IR , up to 30m (98 ft) IR distance
- ▶ Car-Grade LEDs, brighter and uniform light compensation
- ▶ 3D DNR (Digital Noise Reduction)
- ▶ Angle of view(H) 105.2°
- ▶ H.265, H.264, MJPEG
- ▶ Embedded smart algorithm
- ▶ Triple streams
- ▶ 9 : 16 corridor format
- ▶ ONVIF Conformance
- ▶ Wide temperature range : -35 °C to 60 °C (-31 °F to 140 °F)
- ▶ 2-Axis



Camera	
Sensor	1/2.9", 2 Megapixel, Progressive scan CMOS
Shutter	Auto/Manual, 1/6 ~ 1/100000 s
Min. Illumination	Colour: 0.005 Lux (F1.6 , AGC ON) 0 Lux with IR on
Lens Mount	2.8 mm@ F 1.6
Day/Night	IR-cut lter with auto switch(ICR)
S/N	>52 dB
WDR	D-WDR
Video	
Max. Resolution	1920 x 1080
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	1080P (1920x1080): Max. 30fps; 720P (1280x720): Max. 30fps D1 (720x576): Max. 25 fps
Video Streaming	Triple streams
9:16 Corridor Mode	Supported
ROI	Up to 8 areas
HLC	N/A
Defog	Digital Defog
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Smart VCA	
Behavior Detection	Intrusion, crossing line, motion detection
Exception Detection	N/A
Intelligent Identification	Face detection, Defocus, Scene change
Statistical Analysis	People counting
Audio	
Audio Compression	N/A
Two way audio	N/A
Storage	
Edge Storage	Micro SD , up to 128 GB
Network	
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SMTP, 802.1x, SNMP, SSL, TLS
Compatible Integration	ONVIF(Prole S, Prole G), API
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
General	
Power	12 VDC 25%, or PoE(IEEE802.3 af) Power consumption : Max 5.5 W
Dimensions(L x W x H)	108.5 x 81 mm(4.28 x 3.2")
Weight	0.45 kg (0.99 lb)
Working Environment	-35°C to +60°C (-31°F to 140°F), Humidity 95%RH(non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10