



KP-IP911P5SNV

www.kenproctv.com | 02-2220559

Features

- ▶ Day/Night functionality, Starlight Performance
- ▶ Smart IR , up to 30m (98ft) IR distance
- ▶ Angle of view(H)
- ▶ Optical glass window with higher light transmittance
- ▶ HLC (highlight Compensation)
- ▶ 3D DNR (Digital Noise Reduction)
- ▶ H.265, H.264, MJPEG
- ▶ Embedded smart algorithm
- ▶ Triple streams
- ▶ 9 : 16 corridor format
- ▶ ONVIF Conformance
- ▶ Wide temperature range : -35 °C to 60 °C (-31 °F to 140 °F)

SPECIFICATION

| Camera | |
|----------------------------|--|
| Sensor | 1/2.9", 2 Megapixel, Progressive scan CMOS |
| Shutter | Auto/Manual, 1/6 ~ 1/100000 s |
| Min. Illumination | Colour: 0.002 Lux (F1.6 , AGC ON) 0 Lux with IR on |
| Lens | 4.0 mm@ F 1.6 |
| Day/Night | IR-cut filter with auto switch(ICR) |
| S/N | >52 dB |
| WDR | D-WDR |
| Video | |
| Max. Resolution | 1920 x 1080 Pixels |
| Video Compression | Ultra 265, H.265, H.264, MJPEG |
| Frame Rate | 1080P (1920x1080): Max. 30fps; 720P (1280x720): Max. 30fps D1 (720x576): Max. 25 fps |
| Video Streaming | Triple streaming |
| 9:16 Corridor Mode | Supported |
| ROI | Supported |
| HLC | Supported |
| Defog | N/A |
| OSD | Up to 8 OSDs |
| Privacy Mask | Up to 8 areas |
| Smart VCA | |
| Behavior Detection | Intrusion, crossing line, motion detection |
| Exception Detection | Audio detection |
| Intelligent Identification | Face detection, Defocus, Scene change |
| Statistical Analysis | People counting |
| Audio | |
| Audio Compression | N/A |
| Two way audio | N/A |
| Storage | |
| Edge Storage | N/A |
| Network | |
| Protocols | L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP,HTTPS, SMTP, 802.1x, IPv6 |
| Compatible Integration | ONVIF, API |
| Interface | |
| Audio I/O | N/A |
| Alarm I/O | N/A |
| Serial Port | NB/A |
| Network | 1 RJ45 10M/100M Base-TX Ethernet |
| Video Output | N/A |
| General | |
| Power | 12 VDC, or PoE(IEEE802.3 af) Power consumption : Max 6.4 W |
| Dimensions(L x W xH) | 157.3 x 62.4 x 63 mm(6.2 " x 2.5" x 2.5") |
| Weight | 0.45 kg (0.99 lb) |
| Working Environment | -35 ~ °C ~+60 °C (-31 °F ~140 °F), Humidity 95% RH(non-condensing) |
| Ingress Protection | IP67 |

