

Features

- ▶ Day/Night functionality
- ▶ Smart IR , up to 30m (98 ft) IR distance
- ▶ Car-Grade LEDs, brighter and uniform light compensation
- ▶ Angle of view(H)
- ▶ 3D DNR (Digital Noise Reduction)
- ▶ H.265, H.264, MJPEG
- ▶ Embedded smart algorithm
- ▶ Triple streams
- ▶ 9 : 16 corridor format
- ▶ ONVIF Conformance
- ▶ Wide temperature range : -35 °C to 60 °C (-31 °F to 140 °F)
- ▶ 2-Axis



SPECIFICATION

Camera	
Sensor	1/2.7", 2 Megapixel, Progressive scan CMOS
Shutter	Auto/Manual, 1/6 ~ 1/100000 s
Min. Illumination	Colour: 0.005 Lux (F1.6 , AGC ON) 0 Lux with IR on
Lens	2.8 mm@ F 1.6
Day/Night	IR-cut filter with auto switch(ICR)
S/N	>52 dB
WDR	D-WDR
Video	
Max. Resolution	1920 x 1080 Pixels
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	1080P (1920x1080): Max. 30fps; 720P (1280x720): Max. 30fps D1 (720x576): Max. 30 fps
Video Streaming	Triple streaming
9:16 Corridor Mode	Supported
ROI	Supported
HLC	N/A
Defog	N/A
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Smart VCA	
Behavior Detection	Intrusion, crossing line, motion detection
Exception Detection	N/A
Intelligent Identification	Face detection, Defocus, Scene change
Statistical Analysis	N/A
Audio	
Audio Compression	N/A
Two way audio	N/A
Storage	
Edge Storage	N/A
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP,HTTPS, SMTP, 802.1x, IPv6
Compatible Integration	ONVIF, API
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
General	
Power	12 VDC, or PoE(IEEE802.3 af) Power consumption : Max 5.5 W
Dimensions(L x W XH)	126 x 94 (5.0 " x 3.7 ")
Weight	0.33 kg (0.73 lb)
Working Environment	-35 ~ 60 °C (-31 °F ~140 °F), Humidity 95% RH(non-condensing)
Ingress Protection	IP67