


SPECIFICATION

Features

- ▶ VGA and HDMI Output, HDMI at up to 4K(3840 ×2160)
- ▶ H.265 Standard compression algorithm, low bit rate, high picture quality
- ▶ Plug & play with 16 independent PoE network interface
- ▶ Support various VCA detection alarm and VCA search
- ▶ ANR technology to enhance the storage reliability when the network is disconnected
- ▶ Alarm triggering screen popup, buzzer, related record, PTZ preset, pre-alarm, e-mail
- ▶ USB or remote firmware upgrade supported
- ▶ Support ONVIF conformance : Profile S,G,C,Q, A,T



Model(şu)	KP-NVR1625P16NV
Performance	Embedded Pentaplex (Live, Recording, Playback, Backup, Remote Access)
Video/Audio Input	
IP Video Input	16CH
Two-way Audio Input	1CH RCA
Network	
Incoming Bandwidth	112Mbps
Outgoing Bandwidth	96Mbps
Remote Users	128
Video/Audio Output	
HDMI/VGA Output	HDMI 4K(3840x2160@30),4K(3840x2160@60)1024x768@60, 1280x720@60,1280x1024@60,1920x1080@50,1920x1080@60
	VGA 1024x768@60,1280x720@60,1280x1024@60,1920x1080@50, 1920x1080@60
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF
Audio Output	1CH RCA
Synchronous Playback	16CH
OSD Display	Channel name, Date&Time, Record Status, VCA Status etc.
Decoding	
Compression	Ultra265/H.265/H.264
Live View/Playback	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF
Capability	1x4K@30, 2x4MP@30, 3x3MP@25, 4x1080P@30, 8x720P@30, 16xD1
Hard Disk	
SATA	2 SATA interface
Capacity	Up to 8TB for each disk
External Interface	
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, TLS, P2P
Serial Interface	1 x RS-485
USB Interface	Front pane: 1xUSB2.0 Rear panel: 1xUSB2.0
Alarm In	4-CH
Alarm Out	1-CH
PoE(Power Over Ethernet)	
Interface	16 independent 100Mbps PoE network interface
Max. Power	Max 30W for single port Max/Total 240W
Supported Standard	IEEE802.3af/at
General	
Power Supply	220V AC Power
Consumption (Without HDD)	≤ 9 W (without HDD)
Working Temperature	-10 °C ~ + 55 °C (+14 °F ~ +131 °F)
Working Humidity	≤ 90% RH(non-condensing)
Dimensions	380mm x 315mm x 49.1mm (15.0" x 12.4" x 1.9")
Weight(Without HDD)	2.4kg (5.29lb)