


Features

- ▶ Third-party network cameras supported
- ▶ Up to 5 Megapixels resolution recording
- ▶ HDMI and VGA output at up to 1920 × 1080 resolution
- ▶ HDD quota and group management
- ▶ 4/8/16 independent PoE network interfaces
- ▶ FujikoDDNS, KENPRO application for iOS and Android
- ▶ Mac OS, Window OS support
- ▶ Thai & English GUI menu



SPECIFICATION

Model	KP-NVR8004HI
Performance	Embedded Pentaplex
Video/Audio Input	
IP Video Input	4CH
Two-way Audio Input	1-ch, RCA (2.0 Vp-p, 1k)
Network	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	80Mbps
Remote Users	128
Video/Audio Output	
HDMI/VGA Output	HDMI/VGA :1920x1080p /60Hz ,1920x1080p/50Hz ,1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	5MP/4MP/3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Audio Output	1CH, RCA (Linear,1k)
Synchronous Playback	4CH
OSD Display	Channel name, Date&Time, Record Status, VCA Status etc.
Decoding	
Compression	H.264
Live View/Playback Capability	5MP/4MP/3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Hard Disk	
SATA	2 SATA interfaces
Capacity	Up to 4 TB capacity for each HDD
External Interface	
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Protocol	DHCP, TCP/IP, FujikoDDNS, IPv4, IPv6, NTP, HTTP, RTSP, SMTP, HTTPS, HTML, FTP
Serial Interface	1 x RS485
USB Interface	2 x USB 2.0
Alarm In	N/A
Alarm Out	N/A
PoE(Power Over Ethernet)	
Interface	4 independent 100Mbps PoE network interface
Max. Power	Max 30W for single port Max/Total 120W
Supported Standard	IEEE802.3af/at
General	
Power Supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz
"Consumption (Without HDD)"	≤15W
Working Temperature	-10 °C ~+55 °C (+14 °F ~131 °F)
Working Humidity	10% ~ 90%
Dimensions	440 x 261 x 44.5 mm
Weight(Without HDD)	2 kg (Without hard disk)