

## Features

- ▶ HD 1080P Resolution, Image Clear, Delicate
- ▶ Auto electronic shutter time
- ▶ 500M transmission without delay
- ▶ Support coaxial control
- ▶ Support coaxial upgrade



## SPECIFICATION

SPECIFICATION	KP-1913
<b>VIDEO</b>	
Image Sensor	1/2.7" 2.0M Low illumination CMOS sensor
Resolution	1920 x 1080
Lens	HD Lens f3.6mm @F1.8
IRIS Control	N/A
Minimum Illumination	Color:0.01LUX@(F1.2,AGC on);0LUX with IR B/W:0.001LUX@(F1.2,AGC on);0LUX with IR
Electronic Shutter Speed	1/50(1/60)s to 1/10,000s
Day/Night	IR cut lter with auto switch
IR LEDs	42 LEDs; 40 M
Video Out	AHD/TVI/CVI@1080P
<b>FUNCTION</b>	
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	Yes
HSBLC	N/A
Motion Detection	N/A
Privacy Masking	N/A
Day&Night	Auto/Color/B&W
White Balance	Auto/Manual
Digital Noise Reduction	2D/3D DNR
Mirror	Yes
De-fog	N/A
<b>ENVIRONMENTAL</b>	
Out-Door Ready	IP67
Operating Temperature	-10 °C ~ 60 °C (Humidity : 10% ~ 90% RH)
<b>ELECTRICAL</b>	
Power Source	DC 12V(10%)
Power Consumption	Max. 5W
<b>MECHANICAL</b>	
Dimensions(HxWxD)	87mm × 80mm x 281mm
Weight	Around 650g