

KP-1913SV

Features

- ▶ HD 1080P Resolution, Image Clear, Delicate
- ▶ Vari-Focal 2.8-12 mm
- ▶ Auto electronic shutter time
- ▶ 500M transmission without delay
- ▶ Support AHD, TVI, CVI
- ▶ Standard coaxial control
- ▶ Support coaxial upgrade
- ▶ Support XVI



SPECIFICATION

SPECIFICATION	KP-1913SV
VIDEO	
Image Sensor	1/2.8" 2.0M Star- light CMOS sensor
Resolution	1920 x 1080
Lens	Vari-focal 2.8 - 12 mm
IRIS Control	N/A
Minimum Illumination	Color:0.001LUX@(F1.2,AGC on);0LUX with IR B/W:0.0001LUX@(F1.2,AGC on);0LUX with IR
S/N Ratio	N/A
Electronic Shutter Speed	1/50(1/60)s to 1/10,000s
Day/Night	IR cut lter with auto switch
IR LEDs	24SMD; 40 M
Video Out	AHD/TVI/CVI@1080P
FUNCTION	
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	Yes
HSBLC	N/A
Motion Detection	N/A
Privacy Masking	N/A
Day&Night	Auto/Color/B&W
White Balance	Auto/Manual
Digital Noise Reduction	2D/3D DNR
Mirror	Yes
De-fog	N/A
ENVIRONMENTAL	
Out-Door Ready	IP67
Operating Temperature	-10 °C ~ 60 °C (Humidity : 10% ~ 90% RH)
ELECTRICAL	
Power Source	DC 12V(10%)
Power Consumption	Max. 4W
MECHANICAL	
Dimensions(HxWxD)	78mm x 78mm x 239mm
Weight	Around 500g