

Features

- ▶ 5.0MP 1/2.5" Low illumination CMOS sensor
- ▶ HD 5MP Resolution, Image Clear, Delicate
- ▶ HD lens 3.6mm
- ▶ Day/Night(Auto ICR)
- ▶ Auto electronic shutter time
- ▶ 500M transmission without delay
- ▶ IR range 24LEDs 20 meter
- ▶ Support AHD, TVI, CVI, CVBS
- ▶ Standard coaxial control
- ▶ Standard coaxial upgrade



SPECIFICATION

SPECIFICATION	KP-5902
VIDEO	
Image Sensor	5.0MP 1/2.5" Low illumination CMOS sensor
Resolution	2560 x 1920
Lens	HD lens 3.6mm @F1.8
Minimum Illumination	Color:0.01LUX@(F1.2,AGC on);0LUX with IR B/W:0.001LUX@(F1.2,AGC on);0LUX with IR
Electronic Shutter Speed	1/50(1/60)s to 1/10,000s
Day/Night	IR cut lter with auto switch
IR LEDs	24LEDs; 20 M
Video Out	AHD/TVI@5MP, AHD/TVI/CVI@4MP, 960H SD
FUNCTION	
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	N/A
HSBLC	N/A
Day&Night	Auto/Color/B&W
White Balance	Auto/Manual
Digital Noise Reduction	2DNR
Mirror	Yes
Sharpness	Yes
De-fog	N/A
Lens Shading (LSC)	Yes
OSD Language	Multi Language
ENVIRONMENTAL	
Out-Door Ready	IP67
Operating Temperature	-10 °C ~ 60 °C
ELECTRICAL	
Power Source	DC 12V(10%) (Humidity 10% ~ 90% RH)
Power Consumption	Max. 4W
MECHANICAL	
Dimensions(HxWxD)	Ø94.4 × 82.2mm
Weight	Around 300g